

Waidr Three-phase Industrial Vacuum Cleaner



Technical Parameter

| Model | WKM-2210SD | WKM-3010SD | WKM-4010SD | WKM-5510SD | WKM-7510SD |
|---------------------|----------------|------------|------------|------------|------------|
| Voltage (V) | 380 | | | | |
| Power (KW) | 2.2 | 3.0 | 4.0 | 5.5 | 7.5 |
| Airflow (m³/h) | 275 | 318 | 420 | 700 | 700 |
| Vacuum (mbar) | 248 | 270 | 270 | 280 | 300 |
| Noise level (dB) | 65 | 67 | 69 | 71 | 73 |
| Filter area (cm²) | 36000 | | | | |
| Barrel capacity (L) | 100 | | | | |
| Cable length (m) | 5 | | | | |
| Inlet (mm) | 50 | | | | |
| Filter type | HEPA cartridge | | | | |
| Machine weight (kg) | 85 | 109 | 113 | 137 | 146 |
| Machine size (mm) | 1100*600*1450 | | | | |

Features

1. The high pressure side channel blower can work 24h continuously and run smoothly.
2. Famous Control system, with overheating, overload, phase protection function.
3. HEPA Filter: The filter element is made of polyester fiber with filtering area of 36000cm².
4. The machine body is made of mild steel with strong bearing capacity and can adapt to different working conditions.
5. 100L capacity detachable dust bucket, fast and convenient to dump waste.
6. Manual vibrating cleaning system: the machine is equipped with manual vibration device, which can be easily shaken to jet clean the HEPA filter, convenient and fast.

Working Environment

Working area: Heavy industry, large warehouses, workshops, factories, etc., can be matched with production equipment.

Suitable for vacuuming welding slag, grinding rust dust, liquid mixture, sand, particles, metal chips, etc.

| | | | |
|---|---|--|---|
|  |  |  |  |
| HEPA Filter | 50mm Anti-static hose | 50mm Dust brush | Plastic nozzle |

| | | | |
|---|---|--|---|
|  |  |  |  |
| Reducer | 50mm Flat Nozzle | 50mm Round brush | 50mm S-extension tube |

APPLICATION



重工业



大型仓库



车间



工厂